


ITEM: 127003

Product Photo



ERP Energy Label



→ Reinforced 2216 SMD LED inside

12

Key Feature


Product Advantages

- ▶ Reinforced 2216 SMD LEDs inside - 300 LED/m
- ▶ Reinforced 3-OZ (=35/70um) PCBs
- ▶ Excellent Linear Lighting performance
- ▶ Always same BIN for different batches
- ▶ Comply with all kinds of waterproof solutions
- ▶ Mini-Cutting design - Cutting anywhere
- ▶ Max.15m in series connection with power at one end

CCT / COLOR Solution




Waterproof Solution



ITEM: 127003

Drawing:



Notice:

PCB: 8mm width with 3 OZ (35/70um copper);

Size of each section is 6.7mm , and cutting at any place.

LED Strip length's length tolerance is ±0.2%mm, width tolerance is ±0.2mm.

Basic Parameters

Power	12W/m
Voltage	DC-24V
Current	0.5A
PCB	8mm mm width
Max. Connect	5m@12V / 10m@24V (power at one end)

Optical Parameters

CRI	CRI>90
Lumen	1440 LM/w
Efficienc	120 LM/w
LED Type	300pcs 2216 SMD LEDs
LED Chip	Epistar / San-An

Customized Options

PCB color Options	White / Black / Brown
PCB thickness	2-OZ / 3-OZ / 4-OZ
PCB width	3mm-12mm width optional
Logo Printing	Available
Packing/roll	5m / 10m / 15m / 50m

Others

Warranty	5-year
Working Temperature	-35°C to +80°C
Storage Temperature	-35°C to +80°C
Soldering Temperature	300°C for 3 seconds
Thermal Resistane	45°C/W

ITEM: 127003

3M Adhesive Tape



3M 200 LSE Type
(Economy Type)




3M 300 LSE Type
(Mid-quality Type)




3M VHB RED
(High-quality Type)

Packaging


Environment-friendly Paper bag




Environment-friendly Paper Reel



Carton box



Packing Number




Carton box size: 58x36x23cm
 G.W / carton : 12.00 KG/carton
 Quantity /CTN : 400m/carton (40rolls * 10m/roll)

Strip Code :


Part No.	Cutting Length	LEDs/Meter	Power	Voltage	Width	CCT	CRI	Lumen/m
127003	free-cutting	300-LEDs/m	12W	DC-24V	8MM	3000K	>90	1440 LM/m

LED STRIP SOLUTIONS


LED Strip Connectors



LED Strip Cables



Connectors



LED Strip cables

CRI > 95 CRI > 90 CRI > 80

2000K 2700K 3000K 3500K 4000K 4500K 6000K 9000K R G B

ONE BIN
SDCM<3

Various options, optional ordering,
Customizable CCT & BIN

Installation




3M 300LSE




3M VHB Red tape



Heat dissipation



Aluminum Profile



PC Cover

Waterproof



IP-20 (No)



IP-44 (Shrink)



IP-55 (Nano)



IP-65 (Drop)




IP-67 (Tube)



IP-68 (Filling)

Non-waterproof




5m/Reel

10m/Reel

50m/Reel

Waterproof



5m/Reel

10m/Reel

25m/Reel