

ITEM: 127020

PRODUCT PHOTO



Key Feature

Product Advantages

- ▶ Reinforced LEDs inside - 480 LED/m
- ▶ Reinforced 3-OZ (=35/70um) PCBs
- ▶ Excellent Linear Lighting performance
- ▶ Always same BIN for different batches
- ▶ Comply with all kinds of waterproof solutions
- ▶ 8mm width COB design
- ▶ Max.5m in series connection

CCT / COLOR Solution


2000K	2700K	3000K	3500K	4000K	4500K	6000K	9000K
SS	SW	WW	WN	NW	SN	CW	SC

Waterproof Solution

No	Shrink	Nano	Drop	Extrusion	PU fill
IP-20	IP-44	IP-55	IP-65	IP-67	IP-68



Drawing:



Notice:

Size of each section is 12.5mm , and cutting at any place.

LED Strip length's length tolerance is $\pm 0.2\%$ mm, width tolerance is ± 0.2 mm.

Basic Parameters

Power	10W/meter
Voltage	DC-12V / 24V optional
Current/M	0.8A/m@12V / 0.40A/m@24V
PCB	8mm width & 3-OZ
Max. Connect	5m with Power-Feed at one end

Customized Options

PCB color Options	White / Black / Brown
PCB thickness	2-OZ / 3-OZ / 4-OZ
PCB width	3mm-12mm width optional
Logo Printing	Available
Packing/roll	5m / 10m / 15m / 50m

Optical Parameters

Color	RED - 625nm
Efficiency	30LM/W
LUMEN	300LM/m
LED type	480pcs LEDs
LED Chips	Epistar / San-An

Others

Warranty	5-year
Working Temperature	-35°C to +80°C
Storage Temperature	-35°C to +80°C
Soldering Temperature	300°C for 3 seconds
Thermal Resistane	45°C/W

3M Adhesive Tape



3M 200 LSE Type
(Economy Type)




3M 300 LSE Type
(Mid-quality Type)




3M VHB RED
(High-quality Type)

Packaging


Environment-friendly Paper bag




Environment-friendly Paper Reel



Carton box



Packing Number




Carton box size: 58x36x23cm
 G.W / carton : 12.00 KG/carton
 Quantity /CTN : 400m/carton (40rolls * 10m/roll)

Strip Code :


Item Code	LEDs/m	Power	Voltage	PCB	CCT	LM/W	CRI	LM/m
127020	480-LEDs/m	10W/m	DC-12V	8mm	RED	30LM/W	625nm	300 LM/m

LED STRIP SOLUTIONS


LED Strip Connectors




LED Strip Cables




Red/Black Cables - 15cm/20cm




JST-M cables Male/Female - 15cm/1m/2m



DC 5521/25 Male/Female - 15cm/1m/2m




PVC waterproof Male/Female - 15cm/1m/2m



Lucid Male/Female - 15cm/1m/2m

Connectors



LED Strip cables

CRI > 95 CRI > 90 CRI > 80

2000K 2700K 3000K 3500K 4000K 4500K 6000K 9000K R G B

ONE BIN
SDCM<3

Various options, optional ordering,
Customizable CCT & BIN

Installation




3M 300LSE




3M VHB Red tape



Heat dissipation



Aluminum Profile



PC Cover

Waterproof




IP-20 (No)



IP-44 (Shrink)



IP-55 (Nano)



IP-65 (Drop)



IP-67 (Tube)




IP-68 (Filling)


Non-waterproof >



5m/Reel



10m/Reel



50m/Reel


Waterproof >



5m/Reel



10m/Reel



25m/Reel