

- Recommended for the construction of sealed lighting fixtures

APPLICATION

- LED protection and light diffusion in lighting fixtures


MOUNTING

- to the extrusion, by pressing

ADDITIONAL INFORMATION

- standard lengths of KLUŠ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŠ

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Shape	flat
Possibility of bending	yes
UV resistance	yes

Finish	Material	Maximum length on request	Light transmission	Length	Width	Possibility of obtaining a line of light	Ref
frosted	PC	118.1"	65 %	39.4"	0.8"	yes	B17011F_1
				78.9"			B17011F_2
				118.5"			B17011F_3
clear	PC	118.1"	88 %	39.4"	0.8"	no	B17011C_1
				78.9"			B17011C_2
				118.5"			B17011C_3
microprism	PMMA	118.5"	90.5 %	118.5"	0.9"	no	B17011M_3

RELATED PROFILES > ARCHITECTURAL



DIPOK-US
A01233



DIPOKET
A01177



GIZA
A05556



GIZA-DUO-LL
A02162



GIZA-LL
A00758



GIZA-LL-T
A02479



GIZA-LL-UST
A02724N



GLAZA-DUO
A03059



KOZEL
A06454



KOZUS
A07823



KOZUS-CR
A00600



LARKO
A05552



LESTO
A05551A



LIPOD
A05554



LOC-30
A18015




LOKOM
A05553




OPAC-30
A06164

RELATED PROFILES > FACADE




FASKO
A04323

RELATED PROFILES > FOR SCONCES AND WALL LIGHTING



KIDES-DUO
A18032



WERKIN
A18025

RELATED PROFILES > STAIRS ILLUMINATION



STEPUS
A18038