

- Wide range of accessories
- Luminaire direction adjustment
- Small bending radius
- Possibility to use current modules with efficiency up to 190lm/W and CRI>90. Available upon request.

APPLICATION

- main, decorative and functional lighting


MOUNTING

- suspended, to the surface or recessed, using dedicated accessories, a dedicated mounting track, properly selected screws or mounting adhesive
- easy assembly and disassembly by snapping in and out

ADDITIONAL INFORMATION

- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ
- NCS Premium paint option - minimum order quantity 30pcs - available immediately

TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Material	aluminum
Possible fixture IP	20, 65
Possible fixture shapes	linear, polygonal, round
Profile cross-section	rectangular
Width	1"
Height	1"
LED gluing width A	0.9"
Number of LED strips A (0.31" wide)	3
Width of the glow	22 mm
Max power of a single KLUŚ LED strip	7.3 W/ft
Lighting angle adjustment from	0
Lighting angle adjustment up to	240
Dedicated space for power supply	yes
Closet Rated	yes

Color	Length	Ref
■ silver anodized	39.4"	A05554A_1
	78.9"	A05554A_2
	118.5"	A05554A_3
□ white lacquered	118.5"	A05554L100D_3
■ black anodized	118.5"	A05554A07_3

LIPOD Extrusion

Ref. A05554

Possibility of obtaining a line of light	yes
Possibility of bending	yes
Radius of the light arc	yes
Inward	3000 mm
Outdoor	3000 mm
Building type	Commercial, Retail, Entertainment/ Arts, Hotel / Restaurant
Facility zone	office, lobby / foyer, decorative, fitness / spa, media rooms / av
Easy assembly and disassembly by snapping in and out	yes
The cover is cut to the length of the profile	yes
Can be easily connected into runs	yes
Mounting to drywall	yes
Wire out back of extrusion	yes

LINE OF LIGHT TABLE

LED tape	LIGER-22 satin	HS-22 frosted	G-22S satin	G-22R satin
K-2400-24	✓ (2)	X	X	X
K-2300-24	✓ (2)	X	X	X
K-CR-1220-24	✓ (2)	X	X	X
K-CR-1275-24	✓ (2)	X	X	X
K-CRHD-1820-24	✓ (2)	X	X	X
K-CRHD-1910-24	✓ (2)	X	X	X
K-HEHD-0480-24	✓ (2)	X	X	X
K-HEHD-0960-24	✓ (2)	X	X	X
K-HEHD-1440-24	✓ (2)	X	X	X
K-HEHD-1920-24	✓ (2)	X	X	X
K-HEHD-0320-24	✓ (2)	X	X	X
K-RGBW-1920-120-24	✓ (2)	X	X	X
K-RGB-0700-24V	✓ (2)	X	X	X
KWP-RGB-1200-24	✓ (2)	X	X	X
K-22/50-1728-24	✓ (2)	X	X	X
K-27/65-1920-24	✓ (2)	X	X	X
K-18D30-0960-24	✓ (2)	X	X	X
KWP-18D30-0960-24	✓ (2)	X	X	X
K-CRHD-0530-24	✓ (2)	X	X	X
K-HEHD-1440-24-40C	✓ (2)	X	X	X
KWP-GRGBW-1920-120-24	✓ (2)	X	X	X

Description


✔ - Line of Light for a number (X) of rows - Pixel free imaging

X - Visible Dotting from Diodes


HL - Centered Line of Light - Concentrated in middle

HL (X) - Centered Line of Light for a number (X) of rows - Concentrated in middle


Line of Light Guide



Clean Line of Light (Pixel free imaging)



Centered Line of Light



Visible Dotting from Diodes

SAMPLE PROJECTS



SIMILAR EXTRUSIONS



LARKO Extrusion
A05552



LOKOM Extrusion
A05553

SIMILAR EXTRUSIONS > TRIMLESS



KOZEL Extrusion
A06454

RELATED ACCESSORIES > COVERS

NAME	KEY FEATURES	MATERIAL	MATERIAL TRANSMITTANCE	COLOR	REF.	
 - constant voltage version				<div style="display: flex; align-items: center; gap: 10px;"> ■ black </div> <div style="display: flex; align-items: center; gap: 10px;"> □ white </div>	B20L07-ML30-0900-24	
					B20L07-ML40-0900-24	
					B34L07-ML30-0900-24	
					B34L07-ML40-0900-24	
					B48L07-ML30-0900-24	
					B48L07-ML40-0900-24	
					B20L10-ML30-0900-24	
					B20L10-ML40-0900-24	
					B34L10-ML30-0900-24	
					B34L10-ML40-0900-24	
B48L10-ML30-0900-24						
B48L10-ML40-0900-24						
LIGER-22 Cover		- For indoor and outdoor applications - Ease of obtaining a line of light - perfectly diffusing	PC	22 %	black	B17032B
				70 %	satın	B17032S
HS-22 Cover		- For indoor and outdoor applications - UV resistant	PC	65 %	frosted	B17011F
				88 %	clear	B17011C
				90.5 %	microprism	B17011M
G-22S Cover		- indoor use - perfectly diffusing	PMMA	15 %	black	B17013B
				86 %	satın	B17013S
				89 %	semi-transparent	B17013T
G-22R Cover		- indoor use - perfectly diffusing	PMMA	20 %	black	B17006B
				71 %	satın	B17006S
				89 %	semi-transparent	B17006T
				94 %	clear	B17006C

RELATED ACCESSORIES > END CAPS

NAME	MATERIAL	COLOR	REF.
 NEW	PET-G	<input checked="" type="checkbox"/> black	C28286C07
		<input checked="" type="checkbox"/> gray	C28286C02
		<input type="checkbox"/> white	C28286L10
 LIPOD End cap	PP	<input checked="" type="checkbox"/> black	C24004C07
		<input checked="" type="checkbox"/> gray	C24004C02
		<input checked="" type="checkbox"/> silver	C24004L01
		<input type="checkbox"/> white	C24004C10

RELATED ACCESSORIES > PROFILE TECHNICZNE

Name	Material	Color	Ref.
TEKUS Extrusion	aluminum	<input checked="" type="checkbox"/> silver non anodized	A06638V
TEKUS-ZM Extrusion	aluminum	<input checked="" type="checkbox"/> silver non anodized	A01293
TEKNIK-ZM Extrusion	aluminum	<input checked="" type="checkbox"/> silver non anodized	A00399

RELATED ACCESSORIES > RELATED LED > CRI 90+

Name	Key features	IP protection rating	Power consumption	Ref.
KWP-GHD-1910-24 LED tape	- high LED density	65	2.8 W/ft	KWP-GHD22-1910-24 KWP-GHD25-1910-24 KWP-GHD27-1910-24 KWP-GHD30-1910-24 KWP-GHD35-1910-24 KWP-GHD40-1910-24 KWP-GHD50-1910-24
LED tape K-2400-24	- high power	20	7.3 W/ft	K-27-2400-24 K-30-2400-24 K-35-2400-24 K-40-2400-24 K-50-2400-24
KWP-GHD-1640-24 LED tape	- high LED density	65	5 W/ft	KWP-GHD22-1640-24 KWP-GHD25-1640-24 KWP-GHD27-1640-24 KWP-GHD30-1640-24 KWP-GHD35-1640-24 KWP-GHD40-1640-24 KWP-GHD50-1640-24
LED tape K-2400-24	- high power	20	7.3 W/ft	K-27-2400-24 K-30-2400-24 K-35-2400-24 K-40-2400-24 K-50-2400-24

RELATED ACCESSORIES > RELATED LED > HIGH EFFICACY

Name	Key features	IP protection rating	Power consumption	Ref.
K-HEHD-0480-24 LED tape	- CRI over 95 - High Efficacy	20	1.5 W/ft	K-HEHD22-0480-24 K-HEHD25-0480-24 K-HEHD27-0480-24 K-HEHD30-0480-24 K-HEHD35-0480-24 K-HEHD40-0480-24 K-HEHD50-0480-24
K-HEHD-0960-24 LED tape	- CRI over 95 - High Efficacy	20	2.9 W/ft	K-HEHD22-0960-24 K-HEHD25-0960-24 K-HEHD27-0960-24 K-HEHD30-0960-24 K-HEHD35-0960-24 K-HEHD40-0960-24 K-HEHD50-0960-24
K-HEHD-1440-24 LED tape	- CRI over 95 - High Efficacy	20	4.4 W/ft	K-HEHD22-1440-24 K-HEHD25-1440-24 K-HEHD27-1440-24 K-HEHD30-1440-24 K-HEHD35-1440-24 K-HEHD40-1440-24 K-HEHD50-1440-24
LED tape K-HEHD-1920-24	- CRI over 95 - High Efficacy	20	5.9 W/ft	K-HEHD22-1920-24 K-HEHD25-1920-24 K-HEHD27-1920-24 K-HEHD30-1920-24 K-HEHD35-1920-24 K-HEHD40-1920-24 K-HEHD50-1920-24
KWP-HEHD-0480-24 LED tape	- High Efficacy	65	1.5 W/ft	KWP-HEHD22-0480-24 KWP-HEHD25-0480-24 KWP-HEHD27-0480-24 KWP-HEHD30-0480-24 KWP-HEHD35-0480-24 KWP-HEHD40-0480-24 KWP-HEHD50-0480-24
KWP-HEHD-0960-24 LED tape	- CRI over 95 - High Efficacy	65	2.9 W/ft	KWP-HEHD22-0960-24 KWP-HEHD25-0960-24 KWP-HEHD27-0960-24 KWP-HEHD30-0960-24 KWP-HEHD35-0960-24 KWP-HEHD40-0960-24 KWP-HEHD50-0960-24
KWP-HEHD-1440-24 LED tape	- CRI over 95 - High Efficacy	65	4.4 W/ft	KWP-HEHD22-1440-24 KWP-HEHD25-1440-24 KWP-HEHD27-1440-24 KWP-HEHD30-1440-24 KWP-HEHD35-1440-24 KWP-HEHD40-1440-24 KWP-HEHD50-1440-24
K-HEHD-0320-24 LED tape	- CRI over 95 - High Efficacy	20	1 W/ft	K-HEHD22-0320-24 K-HEHD25-0320-24 K-HEHD27-0320-24 K-HEHD30-0320-24 K-HEHD35-0320-24 K-HEHD40-0320-24 K-HEHD50-0320-24

RELATED ACCESSORIES > RELATED LED > RGB / RGB-W / RGB-CTT

Name	Key features	IP protection rating	Power consumption	Ref.
KWP-RGB-1275-12 LED tape		65	4.4 W/ft	KWP-RGB-1275-12
KWP-RGBW-1920-24 LED tape	- RGB	65	5.9 W/ft	KWP-RGBW-1920-24

Name	Key features	IP protection rating	Power consumption	Ref.
KWP-RGB-1920-24 LED tape	- RGB	65	5.9 W/ft	KWP-RGB-1920-24
K-RGB27T65-1200-24 LED tape	- RGB+Tunable White	20	3.7 W/ft	K-RGB27T65-1200-24
LED tape KWP-RGB27T65-1200-24	- RGB+Tunable White	65	3.7 W/ft	KWP-RGB27T65-1200-24
K-RGBW-1920-120-24 LED tape	- RGBW (3000K)	20	5.9 W/ft	K-RGBW-1920-120-24
K-RGBW-1920-160-24 LED tape	- RGBW (3000K)	20	5.9 W/ft	K-RGBW-1920-160-24
KWP-GRGBW-1920-120-24 LED tape	- RGBW (3000K)	65	5.9 W/ft	KWP-GRGBW-1920-120-24

RELATED ACCESSORIES > RELATED LED > ADJUSTABLE WHITE / DIM TO WARM

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-27/65-1920-24V	- Tuneable white 2600K-6500K	20	5.9 W/ft	K-27/65-1920-24
LED tape KWP-27/65-1920-24	- Tuneable white 2600K-6500K	65	5.9 W/ft	KWP-27/65-1920-24
LED tape K-22/50-1728-24V	- Tuneable white 2200K-5000K	20	5.3 W/ft	K-22/50-1728-24
LED tape K-30/18-1770-24V		20	3.5 W/ft	K-30/18-1770-24
LED tape KWP-22/50-1728-24	- Tuneable white 2200K-5000K	65	5.3 W/ft	KWP-22/50-1728-24
LED tape KWP-30/18-1770-24		65	3.5 W/ft	KWP-30/18-1770-24
LED tape KWP-30/18-1770-010-24		65	3.5 W/ft	KWP-30/18-1770-010-24
LED tape K-30/18-1770-010V-24V		20	3.5 W/ft	K-30/18-1770-010V-24V
LED tape KWP-G22/50-1728-24	- Tuneable white 2200K-5000K	65	5.3 W/ft	KWP-G22/50-1728-24

RELATED ACCESSORIES > RELATED LED > CRI 95+

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-CR-1210-24	- CRI over 95	20	1.5 W/ft	K-CR22-1210-24 K-CR25-1210-24 K-CR27-1210-24 K-CR30-1210-24 K-CR35-1210-24 K-CR40-1210-24 K-CR50-1210-24
LED tape K-CR-1220-24	- CRI over 95	20	2.9 W/ft	K-CR22-1220-24 K-CR25-1220-24 K-CR27-1220-24 K-CR30-1220-24 K-CR35-1220-24 K-CR40-1220-24 K-CR50-1220-24
LED tape K-CR-1275-24	- CRI over 95	20	4.4 W/ft	K-CR22-1275-24 K-CR25-1275-24 K-CR27-1275-24 K-CR30-1275-24 K-CR35-1275-24 K-CR40-1275-24 K-CR50-1275-24

LIPOD Extrusion

Ref. A05554

Name	Key features	IP protection rating	Power consumption	Ref.
K-CRHD-1820-24 LED tape	- CRI over 95 - high LED density	20	5.6 W/ft	K-CRHD22-1820-24 K-CRHD25-1820-24 K-CRHD27-1820-24 K-CRHD30-1820-24 K-CRHD35-1820-24 K-CRHD40-1820-24 K-CRHD50-1820-24
K-CRHD-1910-24 LED tape	- CRI over 95 - high LED density	20	2.8 W/ft	K-CRHD22-1910-24 K-CRHD25-1910-24 K-CRHD27-1910-24 K-CRHD30-1910-24 K-CRHD35-1910-24 K-CRHD40-1910-24 K-CRHD50-1910-24
KWP-CR-1220-24 LED tape	- CRI over 95	65	2.9 W/ft	KWP-CR22-1220-24 KWP-CR25-1220-24 KWP-CR27-1220-24 KWP-CR30-1220-24 KWP-CR35-1220-24 KWP-CR40-1220-24 KWP-CR50-1220-24
KWP-CR-1275-24 LED tape	- CRI over 95	65	4.4 W/ft	KWP-CR22-1275-24 KWP-CR25-1275-24 KWP-CR27-1275-24 KWP-CR30-1275-24 KWP-CR35-1275-24 KWP-CR40-1275-24 KWP-CR50-1275-24
KWP-CRHD-1910-24 LED tape	- CRI over 95 - high LED density	65	2.8 W/ft	KWP-CRHD22-1910-24 KWP-CRHD25-1910-24 KWP-CRHD27-1910-24 KWP-CRHD30-1910-24 KWP-CRHD35-1910-24 KWP-CRHD40-1910-24 KWP-CRHD50-1910-24
K-HEHD-1440-24-40C LED tape	- High Efficacy - cold weather -40F	20	4.4 W/ft	K-HEHD22-1440-24-40C K-HEHD25-1440-24-40C K-HEHD27-1440-24-40C K-HEHD30-1440-24-40C K-HEHD35-1440-24-40C K-HEHD40-1440-24-40C K-HEHD50-1440-24-40C
KWP-HEHD-1440-24-40C LED tape	- High Efficacy - cold weather -40F	65	4.4 W/ft	KWP-HEHD22-1440-24-40C KWP-HEHD25-1440-24-40C KWP-HEHD27-1440-24-40C KWP-HEHD30-1440-24-40C KWP-HEHD35-1440-24-40C KWP-HEHD40-1440-24-40C KWP-HEHD50-1440-24-40C
K-CRHD-0530-24 LED tape,	- CRI over 95	20	1.6 W/ft	K-CRHD22-0530-24 K-CRHD25-0530-24 K-CRHD27-0530-24 K-CRHD30-0530-24 K-CRHD35-0530-24 K-CRHD40-0530-24 K-CRHD50-0530-24

RELATED ACCESSORIES > RELATED LED

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape K-0360-24 1.1 W/m, IP20 NEW		20	1.1 W/ft	K-27-0360-24 K-30-0360-24 K-35-0360-24 K-40-0360-24 K-50-0360-24

Name	Key features	IP protection rating	Power consumption	Ref.
LED tape KWP-RGB-1200-24	- RGB	65	3.7 W/ft	KWP-RGB-1200-24
LED tape K-2300-24	- high power	20	7 W/ft	K-30-2300-24 K-40-2300-24
LED tape K-18D30-0960-24	- Dim To Warm LED Stripe	20	2.9 W/ft	K-18D30-0960-24
LED tape KWP-18D30-0960-24		65	2.9 W/ft	KWP-18D30-0960-24

RELATED ACCESSORIES > OTHER ACCESSORIES > MOUNTING BRACKETS

Name	Key features	Material	Color	Ref.
NEW GIP-STN-90D Mounting bracket	- For indoor and outdoor applications	stainless steel	<input type="checkbox"/> silver <input type="checkbox"/> white <input type="checkbox"/> black	C20002N00 C20002L10 C20002L07
NEW Mounting bracket GIP-STN-90G	- For indoor and outdoor applications	stainless steel	<input type="checkbox"/> silver <input type="checkbox"/> white <input type="checkbox"/> black	C20001N00 C20001L10 C20001L07
NEW REGIP-EXT Mounting bracket	- Mounting with angle adjustment function	aluminum, stainless steel	<input type="checkbox"/> black <input type="checkbox"/> white <input type="checkbox"/> gray	C28304C07 C28304C10 C28304N00
GIP-STN Mounting bracket	- For indoor and outdoor applications	stainless steel	<input type="checkbox"/> silver	C24447N00
AM-24 Mounting bracket	- Compatible with 15/16" ceiling grids	steel	<input type="checkbox"/> silver	C24235N00
REGIP Mounting bracket	- Mounting with angle adjustment function	ABS	<input type="checkbox"/> gray	C28057C02
GIP Mounting bracket	- Aesthetic installation of linear fixtures	ASA	<input type="checkbox"/> gray <input type="checkbox"/> black	C24310C02 C24328C07
NEO-ZM-3 Fastener set	- 3 pieces for heavy fixtures	magnet	<input type="checkbox"/> silver	C28105N00
NEO-ZM-4 Fastener set	- 4 pieces for light fixtures	magnet	<input type="checkbox"/> silver	C28106N00
Fastener set NEO-ZM-PLUS-3	- 3 pieces for heavy fixtures	magnet	<input type="checkbox"/> silver	C28107N00
Fastener set NEO-ZM-PLUS-4	- 4 pieces for heavy fixtures	magnet	<input type="checkbox"/> silver	C28108N00

RELATED ACCESSORIES > OTHER ACCESSORIES > SURFACE SPRINGS

Name	Material	Color	Ref.
GP Spring	stainless steel	<input type="checkbox"/> silver	C24500N00

RELATED ACCESSORIES > OTHER ACCESSORIES > LATCHES

Name	Material	Color	Ref.
TEKNIK Latch	PP	<input type="checkbox"/> white	C24003C10

RELATED ACCESSORIES > OTHER ACCESSORIES > EXTRUSION MASKING COVERS

Name	Key features	Material	Color	Ref.
------	--------------	----------	-------	------

Name	Key features	Material	Color	Ref.
MP-22 Masking cover	- Lightproof	PC	<input type="checkbox"/> gray metalized <input type="checkbox"/> gray metalized <input type="checkbox"/> white lacquered <input type="checkbox"/> white lacquered <input type="checkbox"/> black lacquered <input type="checkbox"/> black lacquered	C28261L01_1 C28261L01_0.25 C28261L10_1 C28261L10_0.25 C28261L07_1 C28261L07_0.25

RELATED ACCESSORIES > OTHER ACCESSORIES > ISOLATING BASES

Name	Material	Color	Ref.
FI-6 Isolating bases	nylon	<input type="checkbox"/> white	C28109C00
FI-5 Isolating bases	nylon	<input type="checkbox"/> white	42204
FI-3 Isolating bases	nylon	<input type="checkbox"/> white	42203

RELATED ACCESSORIES > OTHER ACCESSORIES > CONDUCTIVE FASTENERS AND HEADS FOR EXTRUSIONS

Name	Key features	Material	Color	Ref.
PUSZ-ZM Fastener NEW	- Power supply - mounting in the ZM system	stainless steel aluminum aluminum	<input type="checkbox"/> silver <input type="checkbox"/> white lacquered <input type="checkbox"/> black lacquered	C20010N00 C20010L10 C20010L07
BZP-ZZ Head		stainless steel	<input type="checkbox"/> gray	42215
PUSZ-PRET-ZM Fastener	- Power supply cable - mounting in the ZM system	stainless steel, brass, nylon aluminum, brass, nylon aluminum, brass, nylon	<input type="checkbox"/> silver <input type="checkbox"/> white <input type="checkbox"/> black	C28161N00 C28161L10 C28161L07
FI-8-LIN-ZMZ Fastener	- Power supply - mounting in the ZM system	stainless steel, steel, PA, EPDM aluminum, PA, EPDM aluminum, PA, EPDM	<input type="checkbox"/> silver <input type="checkbox"/> white <input type="checkbox"/> black	C28171N00 C28171L10 C28171L07
PUSZ-PRET-ZM Fastener , silver		stainless steel	<input type="checkbox"/> silver	42250
OS22-PRET-Z Fastener	- Power supply rod	PA, stainless steel	<input type="checkbox"/> white <input type="checkbox"/> black	C28186L10 C28186L07
OS22-DUO-PRET-Z Fastener	- Power supply cable, two poles	stainless steel, PA	<input type="checkbox"/> white <input type="checkbox"/> black	C28185L10 C28185L07
OS22-LIN-Z Fastener	- Power supply cable	stainless steel, PA	<input type="checkbox"/> white <input type="checkbox"/> black	C28184L10 C28184L07
OS22-DUO-LIN-Z Fastener	- Power supply cable, two poles	stainless steel, PA	<input type="checkbox"/> white <input type="checkbox"/> black	C28183L10 C28183L07

RELATED ACCESSORIES > OTHER ACCESSORIES > FASTENERS AND HEADS FOR EXTRUSIONS

Name	Key features	Material	Color	Ref.
BZP Head		stainless steel	<input type="checkbox"/> silver	C28113N00
FI-8-LIN-ZM Fastener	- Installation in the ZM system	stainless steel, PA	<input type="checkbox"/> silver <input type="checkbox"/> white <input type="checkbox"/> black	C28170N00 C28170L10 C28170L07
FI-10-ZM-P Fastener	- Cross mounting	stainless steel	<input type="checkbox"/> silver	C28117N00
FI-10-ZM-W Fastener		stainless steel	<input type="checkbox"/> silver	C28116N00
FI-8-PRET-ZM Fastener	- Installation in the ZM system	Materiał, Material, multiselect	<input type="checkbox"/> silver <input type="checkbox"/> white <input type="checkbox"/> black	C28189N00 C28189L10 C28189L07

RELATED ACCESSORIES > OTHER ACCESSORIES > COUPLERS

Name	Key features	Material	Color	Ref.
X135 Coupler	- Facilitates building lighting structures	aluminum	■ silver	X135
T135L Coupler	- Facilitates building lighting structures	aluminum	■ silver	T135L
T135R Coupler	- Facilitates building lighting structures	aluminum	■ silver	T135R
T90 Coupler	- Facilitates building lighting structures	aluminum	■ silver	T90
L135 Coupler	- Facilitates building lighting structures	aluminum	■ silver	L135
L135PW Coupler	- Facilitates building lighting structures	aluminum	■ silver	L135PW
L135PZ Coupler	- Facilitates building lighting structures	aluminum	■ silver	L135PZ
L90 Coupler	- Facilitates building lighting structures	aluminum	■ silver	L90
L90PW Coupler	- Facilitates building lighting structures	aluminum	■ silver	L90PW
L90PZ Coupler	- Facilitates building lighting structures	aluminum	■ silver	L90PZ
X90 Coupler	- Facilitates building lighting structures	aluminum	■ silver	X90




RELATED ACCESSORIES > OTHER ACCESSORIES > SUSPENSION AND MOUNTING SETS

Name	Key features	Material	Color	Ref.
FI-8-ZM-1 Fastener set NEW	- Power supply, for wall and drywall, in the ZM system	stainless steel, aluminum	■ silver □ white lacquered ■ black lacquered	C28134N00 C28134L10 C28134L07
FI-8-ZM-2 Fastener set NEW	- Convenient cable length adjustment, in the ZM system	stainless steel, aluminum	■ silver □ white lacquered ■ black lacquered	C28135N00 C28135L10 C28135L07
Fastener set PUSZ-ZM-1 NEW	- Power supply, for wall and drywall, in the ZM system	stainless steel, aluminum	■ silver □ white lacquered ■ black lacquered	C28130N00 C28130L10 C28130L07
Fastener set PUSZ-ZM-2 NEW	- Convenient cable length adjustment, in the ZM system	stainless steel, aluminum	■ silver □ white lacquered ■ black lacquered	C28131N00 C28131L10 C28131L07
RG-1 Fastener set	- Cable adjustment at the ceiling, cable included	brass	■ silver glossy ■ silver satin □ white colored ■ black colored	C28230P00 C28230P01 C28230L10 C28230L07

RELATED ACCESSORIES > OTHER ACCESSORIES > SECURITY AND BLOCKS

Name	Key features	Material	Color	Ref.
Block ZM, gray	- Accessory locking in the ZM system	silicon	■ gray	C28194N00





RELATED ACCESSORIES > OTHER ACCESSORIES > CANOPIES

Name	Key features	Material	Color	Ref.
Fi-60mm Canopy	- Convenient cable length adjustment, in the ZM system	steel	 gray lacquered	C24540L01
			 white lacquered	C24540L10
			 black lacquered	C24540L07



RELATED ACCESSORIES > OTHER ACCESSORIES > ADDITIONAL ITEMS

Name	Material	Ref.
8x1,6 Gland	rubber	C42290C07
M8x1 Gland	brass	C42265N00

RELATED ACCESSORIES > OTHER ACCESSORIES > CONNECTORS

Name	Material	Color	Ref.
ZM Connector	stainless steel	 silver	42716
			42717
			42720
			42728
			C28070N00
			C28071N00
			C28072N00
			C28073N00
			C28074N00
			C28075N00
C28243N00			
ZM-NA Connector	stainless steel	 silver	42305
			42339
			42723
			42724
			42725
			C28242N00
ZM-PION Connector	stainless steel	 silver	42314
			42316
			42320
			42718
			42719
			C28084N00
			C28085N00
			C28086N00
			C28087N00
C28088N00			
ZM-NA-PION Connector	stainless steel	 silver	42315
			42317
			42321
			42726
			42727

RELATED ACCESSORIES > OTHER ACCESSORIES

Name	Material	Color	Ref.
Connector ZM-Y	stainless steel	 silver	C28082N00
ZM-X Connector	stainless steel	 silver	C28079N00
			C28080N00
			C28081N00

LIPOD Extrusion

Ref. A05554

Name	Material	Color	Ref.
ZM-T Connector	stainless steel	 silver	C28076N00 C28077N00 C28078N00

RELATED ACCESSORIES > ELECTRONICS > SWITCHES

Name	Key features	IP protection rating	Ref.
Proximity switch UNI	- touchless switch - width only 7mm	20	E61579